

# Oil & Gas Producer Increased Production and Reduced Operating Expenses with Vortex Technology

## RESULTS

- Increased oil and gas production
- Decreased field operating expenses
- Improved reliability of well test and production data
- Improved the health of personnel, safety of assets, and protection of the environment by lengthening maintenance intervals



*Well test data is now more readily available to help determine if the well is producing as expected.*

## APPLICATION

Production & test separator liquid flow lines

## APPLICATION CHARACTERISTICS

20 - 1400 psi, 70 - 150 °F (21 - 66 °C)

## CUSTOMER

A leading independent oil and gas producer with operations primarily focused in the United States and Canada.

## CHALLENGE

This oil and gas producer has seen operating expenses skyrocket the past 10 years, increasing almost 700%. This is not only due to the increased activity in the upstream segment and rising inflation costs within the industry, but the utilization of older technology such as mechanical meters.

All of their producing wells flow into either a production or test separator to separate gas from liquids. Then, the liquids flow out of the separator where the flow rates have traditionally been measured by turbine meters.

Due to debris in flow lines, mechanical meters required extensive maintenance to replace or clean the rotating blades. When these meters fail on test or production separators, the liquid production flow rates are not measured and must be inferred.

This resulted in unknown daily volumes until the next time it was placed on a scheduled well test. This failure is very costly, especially when the well experienced high water or low oil production and well intervention was required.



*The Rosemount 8800 Vortex Flowmeter.*

**ROSEMOUNT**<sup>®</sup>

For more information:  
[www.rosemount.com](http://www.rosemount.com)

  
**EMERSON**<sup>™</sup>  
Process Management

Replacement or cleaning of internal parts required mechanical meters to be removed from the line, typically once per year. Maintenance personnel would spend more time near open production lines, resulting in increased safety, health, and environmental risks.

### SOLUTION

The Rosemount 8800 Vortex Flowmeter helped solve the pains associated with this separator application. Operating costs were reduced with vortex technology with its longer operation lifetime relative to mechanical meters. Because the Rosemount 8800 has no moving parts, no routine replacement or cleaning is necessary. This reduced the amount of time maintenance personnel spent near open production lines, decreasing the risk involved with safety, health, and environmental concerns. In addition, it has a unique meter body design, which reduces plugging from sand and other material and also comes in a variety of connections and sizes, creating a drop-in replacement of most turbine meters.

The ease of replacement and long life of the Rosemount 8800 allowed for better availability of production and well test data for this producer. Production engineers now have the well performance data to determine if the well is producing as expected, or if it is producing excessive water. Field operations were also improved by reducing the time spent maintaining mechanical meters and reallocating this time towards other tasks, which increased production.

### RESOURCES

#### Emerson Process Management Oil and Gas Industry

<http://www2.emersonprocess.com/en-US/industries/oil-gas/Pages/OilandGas.aspx>

#### Rosemount 8800 Vortex Flowmeter

<http://www2.emersonprocess.com/en-US/brands/rosemount/Flow/Vortex-Flowmeters/8800-Series/Pages/index.aspx>

The contents of this publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which can be found at [www.rosemount.com/terms\\_of\\_sale](http://www.rosemount.com/terms_of_sale). We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

The Emerson logo is a trade mark and service mark of Emerson Electric Co.  
Rosemount and the Rosemount logotype are registered trademarks of Rosemount Inc.  
PlantWeb is a registered trademark of one of the Emerson Process Management group of companies.  
All other marks are the property of their respective owners.

#### Emerson Process Management

**Rosemount Incorporated**  
8200 Market Boulevard  
Chanhassen, MN 55317 USA  
[www.rosemount.com](http://www.rosemount.com)  
Tel (USA) +1 800 522 6277  
Tel (International) +1 (303) 527 5200  
Fax +1 (303) 530 8459

#### Emerson Process Management

Blegistrasse 23  
P.O. Box 1046  
CH 6341 Baar  
Switzerland  
Tel +41 (0) 41 768 6111  
Fax +41 (0) 41 768 6300

#### Emerson FZE

P.O. Box 17033  
Jebel Ali Free Zone  
Dubai UAE  
Tel +971 4 811 8100  
Fax +971 4 886 5465

#### Emerson Process Management Asia Pacific Private Limited

1 Pandan Crescent  
Singapore 128461  
T (65) 6777 8211  
F (65) 6777 0947  
[Enquiries@AP.EmersonProcess.com](mailto:Enquiries@AP.EmersonProcess.com)

#### Emerson Process Management Latin America

**Multipark Office Center**  
Multipark Office Center  
Turrubares Building, 3rd & 4th floor  
Guachipelin de Escazu, Costa Rica  
T+(506) 2505-6962  
[international.mmicam@emersonprocess.com](mailto:international.mmicam@emersonprocess.com)

**ROSEMOUNT**<sup>®</sup>

For more information:  
[www.rosemount.com](http://www.rosemount.com)



**EMERSON**<sup>™</sup>  
Process Management