CERTIFICATE OF COMPLIANCE

 Certificate Number
 20140918-E79070

 Report Reference
 E79070-19880511

 Insura Data
 2014-SERTEMBER

Issue Date 2014-SEPTEMBER-18

Issued to: TOPWORX INC

3300 FERN VALLEY RD LOUISVILLE KY 40213

This is to certify that representative samples of

AUXILIARY DEVICES FOR USE IN HAZARDOUS LOCATIONS and AUXILIARY DEVICES FOR USE IN

ZONE CLASSIFIED HAZARDOUS LOCATIONS

CERTIFIED FOR CANADA

See Addendum page for models

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1203, Explosion-Proof and Dust-Ignition-Proof Electrical

Equipment for Use in Hazardous (Classified) Locations; UL 50E, Enclosures for Electrical Equipment, Environmental

Considerations

CSA C22.2 No. 25-1966, Enclosures for use in Class II

Groups E, F, and G Hazardous Locations;

CSA C22.2 No. 30-M1986, Explosion-proof enclosures for

use in Class I Hazardous Locations;

CSA-C22.2 NO. 60079-0:11, Explosive Atmospheres - Part 0:

Equipment - General Requirements:

CSA-C22.2 NO. 60079-11:14, Explosive Atmospheres - Part

11: Equipment Protection by Intrinsic Safety "i"

Additional Information: See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada. The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and

"US" identifiers: ^c(U) us the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.

William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus



CERTIFICATE OF COMPLIANCE

 Certificate Number
 20140918-E79070

 Report Reference
 E79070-19880511

 Issue Date
 2014-SEPTEMBER-18

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

US Listed Only:

Proximity switches for use in Class I, Groups A, B, C, and D; Class II, Groups E, F, and G; and Class III Hazardous Locations.

Model 11, followed by 1, 3, 5, or 6; followed by 1, 2, or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by 3; followed by letters and/or numbers.

Model 21, followed by 1, 3, 5, or 6; followed by 1, 2 or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by 3; followed by letters and/or numbers.

Proximity switches for use in Class I, Division 2, Groups A, B, C, and D; Class II, Division 2, Groups F, and G; and Class III Hazardous Locations.

Model 11, followed by 1, 3, 5, or 6; followed by 1, 2, or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by E; followed by letters and/or numbers.

Model 21, followed by 1, 3, 5, or 6; followed by 1, 2 or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by E; followed by letters and/or numbers.

William R. Carney

William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, pleas contact a local UL Customer Service Representative at www.ul.com/contactus

(U)

CERTIFICATE OF COMPLIANCE

Certificate Number 20140918-E79070

Report Reference E79070-19880511

Issue Date 2014-SEPTEMBER-18

Canadian Listed Only:

Proximity switches for use in Class I, Groups A, B, C, and D; Class II, Groups E, F, and G; and Class III Hazardous Locations.

Model 11, followed by 1, 3, 5, or 6; followed by 1, 2, or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by 4; followed by letters and/or numbers.

Model 21, followed by 1, 3, 5, or 6; followed by 1, 2 or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by 4; followed by letters and/or numbers.

Proximity switches for use in Class I, Division 2, Groups A, B, C, and D; Class II, Division 2, Groups F, and G; and Class III Hazardous Locations.

Model 11, followed by 1, 3, 5, or 6; followed by 1, 2, or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by 0 or 6; followed by letters and/or numbers.

Model 21, followed by 1, 3, 5, or 6; followed by 1, 2 or 7; followed by 1, 2, 3, 4, or 5; followed by 2 or 4; followed by 0 or 6; followed by letters and/or numbers.

Proximity switches for use in Class I, Zone 0, Ex ia IIC; Ex ia IIIC Hazardous Locations.

Model 11, followed by 1, 3, 5, or 6; followed by 1, 2, or 7; followed by 1, 2, 3, 4, or 5; followed by 1, 2, 3, or 4; followed by F, G, or H, followed by letters and/or numbers, followed by Z. Intrinsically safe when connected in accordance with control drawing no. ES-04728-1.

Model 21, followed by 1, 3, 5, or 6; followed by 1, 2 or 7; followed by 1, 2, 3, 4, or 5; followed by 1, 2, 3, or 4, followed by F, or H, followed by letters and/or numbers, followed by Z. Intrinsically safe when connected in accordance with control drawing no. ES-04728-1.

William R. Carney

William R. Carney, Director, North American Certification Programs

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

