AMS Device Manager Release Timeline

**Version 1.0
(October 4, 1996)**
• HART devices (8 total)

**Version 1.2
(April 22, 1997)**
• More HART devices
  (22 total)
• Elcon 1700 multiplexer
  and PCMIA HART
  modem

**Version 1.4
(August 9, 1999)**
• More HART devices, including non
  Emerson vendors for the first time
• Support for additional calibrators
  including Fluke, Druck, and the
  Rosemount Validator
• RBMWare Interface
• Support for MTL & Pepperl + Fuchs
  multiplexers
• Conventional device support for
  pressure, temperature, flow, valves,
  and generic
• DeltaV System Interface
• Calibration Manager
• Y2K compliance

**Version 6.5
(January 23, 2004)**
• Fieldbus support for
  Ovation

**Version 6.1
(March 31, 2003)**
• AMS Web functionality
  and Web services

**Version 8.0
(September 14, 2006)**
• Smart Wireless System Interface
• Enhanced fieldbus support with
  DeltaV

**Version 10.0
(November 19, 2008)**
• Easy Device Replacement and Commissioning
• New Alert Monitor that supports latching and
  filtering of alerts
• Drag and drop provisioning of wireless devices
• Support all HART devices registered with
  HART Foundation
• Support for the AMS Wireless, AlertTrack, and
  Meter Verification SNAP-ONs
• Support for Windows Vista Business and
  Windows Server 2008

**Version 11.0
(May 4, 2010)**
• DeltaV CHARM I/O
  and S Series hardware
• PROFIBUS DP support
  with DeltaV
• Launch of Device
  Dashboards

**Version 11.5
(September 30, 2011)**
• Windows 7 and Server
  2008 64-bit operating
  systems and Windows
  7 Enterprise edition

**Version 12.5
(November 15, 2013)**
• New FF templates and Bulk
  Transfer
• New Device Configuration
  Reports tool
• Windows 8 and Server 2012
  operating systems

**Version 13.1.1
(January 2017)**
• Localized for Japanese, Russian,
  French, Chinese
• Optimized Alert Definition in
  device install kits
• Option for disabled alerts not in
  Audit Trail
• Support for OpenEnterprise 3.2.x
• User Configuration Security
• Support for Windows Active
  Directory

**Version 13.5
(May 2017)**
• AMS Device View 1.0
• AMS Trex Auto Sync
• Enhanced User
  Configuration
  Reporting

1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018

**Version 1.1
(February 6, 1997)**
• More HART devices
  (15 total)

**Version 1.3
(July 1, 1998)**
• AMS ValveLink SNAP-ON
  application
• More HART devices (33 total)
• PROVOX and RS3 System
  Interface

**Version 5.0
(August 30, 2000)**
• 188 additional devices from
  38 device manufacturers
• 5,000 tag count support
• New multiplexers: Elcon,
  STAHL, and MTL
• New Beamex calibrator
• Audit Trail
• Alert Monitor

**Version 6.0
(June 14, 2002)**
• 63 new HART devices
• 20,000 tag count support
• 13 conventional device templates
• 13 calibrators and 5 multiplexer
  manufacturers
• Ovation System Interface
• Calibration Assistant SNAP-ON

**Version 6.2
(October 6, 2003)**
• The Handheld Communicator
  Interface adds the 375 Field
  Communicator
• HART Over PROFIBUS
  Interface
• AMS ValveLink Batch Runner
  & PD scheduler
• Electronic signatures

**Version 7.0
(October 1, 2005)**
• The DeltaV and Ovation System
  Interfaces add support for fieldbus
  devices
• Support for DeltaV Safety
  Instrumented Systems (SIS)
• Access all devices in a distributed
  system from any station
• Calibration support for fieldbus and
  flow devices

**Version 9.0
(January 8, 2007)**
• Enhancements to
  DeltaV System
  Interface

**Version 10.1
(April 1, 2009)**
• Support of cross-
  block device
  descriptors for
  FOUNDATION
  Fieldbus devices
• Support for
  HART revision 7
  devices

**Version 10.5
(October 9, 2009)**
• Smart Wireless THUM Adapter
• 475 Field Communicator
  Bluetooth interface
• Localization into Japanese,
  Russian, and German
• Siemens SIMATIC PCS 7
  Interface

**Version 11.1
(July 15, 2010)**
• Guardian support for
  AMS Device Manager
• DeltaV WIOC Support

**Version 11.1.1
(December 28, 2010)**
• Multi-byte characters
  on supported non
  English operating
  systems

**Version 12.0
(November 2, 2012)**
• PROFIBUS PA support
• Integration of Det-Tronics EQP system
• DTM Launcher Application
• Calibration Connectors for Beamex
  CMX and AMS Suite APM
• Automatic DD updates with Guardian
• ABB 800xA interface

**Version 13.0
(April 30, 2015)**
• Enhanced Security by
  Plant Area
• HART Templates and
  Bulk Transfer

**Version 14.0
(June 2018)**
• AMS Device View
  2.0 and Project
  designation
• Added Bulk Transfer
  fields
• Ability to
  lock/unlock devices
• Added Optimized
  device install kits for
  alert reduction, all
  Emerson devices
  optimized