DeltaV[™] Simulate

- Allows DeltaV[™] configuration on a single PC or in a multi-node system
- Provides integrated simulation of control system (BPCS) and safety system (SIS)
- Enables development and testing of batch and continuous control applications in an off-line simulation environment
- Supports engineering check out, validation, and testing of field devices and OPC interfaces
- Provides an ideal environment for operator training and process simulation
- Enhances training with simulation playback
- Reduces training and testing effort
- Supports rigorous testing of control configurations, operator graphics
- Supports virtualization of DeltaV workstations and control hardware



DeltaV[™] Simulate Suite for Training and Development.

Introduction

Don't delay development of your automation system configuration, logic checkout, and operator training until your automation system is delivered. Do it now with the $DeltaV^{m}$ Simulate suite of products.

DeltaV Simulate lets you use all DeltaV software for training and development without purchasing duplicate system hardware. This means you can use exactly the same software provided with your actual DeltaV system at a fraction of the system footprint and cost. With the simulate suite you can also explore features of the DeltaV system that you have not yet purchased. Get the most out of your process simulation package using the features of DeltaV SimulatePro. Execute dynamic process simulation using DeltaV control modules or with simulation packages such as Mimic[™] that access data via OPC. With DeltaV SimulatePro, you can control DeltaV execution with speed-up, slow-down, save and restore functionality.

DeltaV Simulate also supports SIS simulation with a complete simulation environment for design, testing, and training of both BPCS and SIS systems.





Benefits

Allows DeltaV configuration on a single PC or in a multi-node system. All features supported by the DeltaV system—such as continuous control, batch control, advanced control and the associated workstation displays, alarms, and historian data collection—may be configured without the need for DeltaV hardware or licenses. By having access to all software, you can try every one of the powerful DeltaV capabilities in your control strategies.

Provides integrated simulation of basic process control system (BPCS) and safety instrumented systems (SIS). Now all of your BPCS and SIS control modules can be designed and tested on a common simulation platform for rigorous checkout and training.

Enables development and testing of batch and continuous control applications in an off-line workstation environment.

Check out control logic and operator interface using controller software that runs in a stand-alone ProPlus, Application Stations, or virtual machine controllers. After developing and testing your software configuration in DeltaV Simulate, you can transfer the configuration to your online system using the standard DeltaV export/import utilities.

Supports testing of smart field devices and OPC interfaces.

DeltaV Simulate Multi-node supports the addition of DeltaV controllers, allowing you to checkout a certain type of field devices, incorporate DeltaV hardware for maintenance training, and test your control configurations with smart field devices. DeltaV Simulate also supports all DeltaV OPC features for development and testing of applications that execute in the DeltaV Application Station.

Provides an ideal environment for operator training and process simulation. DeltaV Simulate uses the same configuration and operator graphics used by your on-line DeltaV system, and is easily integrated with dynamic process simulation to provide a realistic training environment. Process simulation may be done using DeltaV function blocks or by incorporating an OPC-compliant process simulation package such as Mimic.

Enhances training with simulation scenarios and playback. DeltaV SimulatePro significantly enhances the operator training experience by allowing the instructor to save, restore, and playback operator entries during training sessions.

Reduces training and testing effort. The DeltaV SimulatePro interface allows modules in a workstation to be initialized and set up for simulation with a single easy to use interface. Also, through this interface, the module may be easily set to execute faster/slower than real time. These features reduce the time and effort required to perform operator training or control design evaluation.

Supports rigorous testing of control configurations,

operator graphics. Easily simulate process I/O for classic I/O, CHARMS I/O and Ethernet I/O cards for non-intrusive control system testing prior to field commissioning, without any changes to your control system configuration.

Supports virtualization of DeltaV workstations and control

hardware. Reduce equipment costs and increase flexibility with virtual workstations, controllers, logic solvers, CHARMS I/O cards and Ethernet I/O cards. DeltaV Simulate virtualization is made easy with DeltaV Virtual Studio.

Product Description

DeltaV Simulate Standalone

With DeltaV Simulate Standalone or DeltaV SimulatePro Standalone, all DeltaV system features are available in a single PC environment that acts as a ProfessionalPLUS Station. Using your PC, it is possible to create controllers and workstations that will be on your DeltaV system. DeltaV devices may be configured offline, including any fieldbus devices that will be included in your automation system.

With DeltaV Simulate, the transition between on-line and off-line control is easy. On-line modules are normally assigned to a controller and used to implement DeltaV system specific monitoring, process control, and calculation functions. Also, modules designed for performance calculations are normally assigned to the DeltaV Application Station. With DeltaV Simulate, process control and calculation functions are easily tested by simply reassigning the associated control modules to your PC.



Modules assigned to the workstation for execution.

All function blocks that access process inputs and outputs are designed to support simulation. A simulation parameter is included in each of these blocks that may be used to enable simulation capability. When simulation is enabled, the value and status of the input may be manually entered or supplied by another function block or application.



Simulation support provided by all DeltaV I/O blocks.

When your Simulate workstation is downloaded, the assigned modules will automatically begin to execute at the assigned execution rate. The execution of a module in the PC may be examined from Control Studio's online mode.

DeltaV Simulate and SimulatePro support the full range of advanced control products normally requiring additional system licenses. This allows you to try out products like DeltaV InSight, DeltaV Fuzzy and DeltaV PredictPro in your simulation environment.

The following example shows the online view of a module in Control Studio where the process is simulated using DeltaV function blocks.



Module execution may be simulated and examined.

The execution engine in the PC is limited by memory. You will be notified when this limit is exceeded. Typically, the modules that would be assigned to a single DeltaV controller can be assigned and downloaded to your PC for execution.

Application packages that support an OPC interface may be used in the DeltaV Simulate environment. For example, the OPC version of the Mimic process simulation may be used with DeltaV Simulate for automation system checkout and operator training. The Mimic OPC interface uses the simulate capability of the DeltaV system and I/O blocks.



Process simulation may interface to DeltaV using OPC.

DeltaV Simulate Multi-node

DeltaV Simulate Multi-node allows you to add other nodes to your simulation environment. Application Stations may be added to run control modules for distributed control execution. Operator Stations and controllers may be added to support your training or development system requirements.

A special access key and licenses are utilized by a DeltaV Simulate system. With a DeltaV Simulate Standalone license, communication with other DeltaV nodes is not supported. With DeltaV Simulate Multi-node licenses, connections to an off-line DeltaV network are supported. A license is required for each workstation in the DeltaV Simulate Multinode environment. DeltaV controllers and I/O cards may be connected to this network without any additional DST licenses. DeltaV Simulate Multi-node also supports the use of real and virtual machine controllers with simulated I/O for rigorous testing of your control configurations. For real controllers, classic I/O simulation is easily implemented via a Virtual I/O Module (VIM) which connects directly to the DeltaV controller I/O bus. For real and virtual machine controllers, process simulation is supported using either an actual CHARMS I/O card in simulate mode, or via a virtual CHARMS I/O card running on a host computer connected to the DeltaV network. Starting in v14.3, you can also simulate I/O signals in virtual machine controllers using DST tag name references. *Refer to DeltaV Virtual CHARMS I/O Card Simulation and DeltaV Virtual Machine Controller Simulation product data sheets for more information.*

DeltaV SimulatePro

You can use DeltaV SimulatePro Standalone on a single PC, or assign a SimulatePro Multi-node license to a ProfessionalPLUS and/or Application Workstation in a DeltaV Simulate Multi-node system.

When SimulatePro capability is assigned to a workstation, you may coordinate execution of the DeltaV control modules running in the workstation with a dynamic process simulation package via OPC.

The number of control modules that can be simulated in a workstation with a SimulatePro license is limited only by the memory and processing power of the workstation. A node with SimulatePro capability assigned to it can simulate execution, in real-time, of the modules that would be assigned to approximately four MQ controllers (depending on the controllers' loading). Workstation loading, which is a function of the real-time execution multiplier setting, more than doubles at 2X execution speed.



DeltaV Simulate Multi-node for training and development systems.

Application packages that support an OPC interface may be used in the DeltaV SimulatePro environment. For example, Emerson's Mimic dynamic process simulation software may be used with DeltaV Simulate. The Mimic interface uses the simulation capability of DeltaV I/O function blocks.



Use Mimic process simulation with DeltaV SimulatePro.

A process simulation package used with DeltaV SimulatePro may read and write the parameters assigned to the module node through OPC. By writing to these parameters, the simulation package may enable/disable simulation in all I/O blocks with a single request. All dynamic blocks assigned to the node may be initialized with a single request. Also, these modules may be set to execute faster or slower than real time.

DeltaV SimulatePro has additional features to greatly enhance operator training. With SimulatePro you can snapshot, save, and restore your entire control simulation. With a single click of a mouse, one or all of the workstations in your system will freeze control execution and save every single control parameter away to be recalled later. After finishing a training scenario, an instructor can use this feature to load initial conditions back into any or all of your workstation control modules.

DeltaV SimulatePro also lets you record and playback all of the operator entries made during a simulation session. This means that after a training exercise you can go back and restore the simulation and automatically playback the simulation with all the operator entries. An instructor can also stop the simulation where an operator error was made, and allow the operator to resume operation before the error. This powerful functionality makes DeltaV SimulatePro an absolute must for operator training systems.



Use SimulatePro Interface to save, restore, and play back operator entries.

For control system checkout, DeltaV SimulatePro enables simulation and checkout of control strategies using Fieldbus and external I/O references. A Simulate Conversion utility is provided with SimulatePro that converts Fieldbus control blocks to their equivalent DeltaV function blocks, and external I/O references are mapped to internal DeltaV function block parameters so they can be simulated.

DeltaV v14 Simulate Enhancements

Starting in DeltaV v14.3 the following enhancements are available:

DST I/O Simulation

With DST I/O Simulation you can simulate I/O signals (for conventional and several types of bussed I/O) in a virtual machine controller by reading and writing to Device Signal Parameter using DST tag name references. Access to Device Signal Parameters is provided through a DeltaV I/O Simulate Application or via OPC. Simulation via DST tag names enable you to read and write device parameters without knowing physical I/O assignments. For more information see product data sheet for DeltaV Virtual Machine Controller Simulation.

Advanced Batch Simulation

Starting with v14, DeltaV SimulatePro supports "save and restore" of Batch Executive operations and modules using phase algorithms. Prior to v14, SimulatePro does not support "save and restore" of Batch Executive or modules using phase algorithms, which includes Unit Modules, Equipment Modules, Phase Logic Modules (PLMs), and Phase Classes.

Enhanced Save and Restore

DeltaV SimulatePro is enhanced in v14 to provide selective save and restore operations using XML initial condition files. This feature helps you restore simulation scenarios after control configuration changes have been made to your system.

DeltaV SIS Simulation

DeltaV Simulate supports both traditional SIS Logic Solvers (SLS1508) and SIS with Electronic Marshalling using Charms Smart Logic Solvers (CSLS). With DeltaV SIS simulation you can design and test a safety instrumented system without logic solver hardware. DeltaV SIS simulation uses the exact same logic solver modules and operator graphics that our used in the on-line system, enabling rigorous testing of configurations and operator interfaces prior to field implementation.

Simulation for DeltaV SIS Logic Solvers (SLS1508)

DeltaV Simulate for SIS Logic Solvers supports simulation of up to 32 logic solvers per workstation, with up to 32 workstations on a multi-node simulation system. Simulated logic solvers are easily configured to run directly in the ProfessionalPLUS and Application Stations, and support both simplex and redundant configurations. Simulation for SIS Logic Solvers also supports both local and global peer-to-peer communications of secure parameter references.

Transferring logic configurations between on-line and simulation environments is easy using DeltaV export and import functions. For additional SIS integrity, Simulate for SIS Logic Solvers supports CRC validation to insure configurations are identical between on-line and testing environments. DeltaV Simulate for SIS Logic Solvers also provides the ability to write simulated process inputs to virtual SLS module input parameters, without any manual confirmation. Process values, signal status, and secure global parameters may be easily entered via an I/O simulator for rigorous logic checkout.

DeltaV Simulate for SIS Logic Solvers also supports the use of comprehensive process simulators. A SIS network OPC server provides the ability to read SIS output parameters and write SIS input parameters by external process simulators, like Mimic.

Note: DeltaV Simulate for SIS Logic Solvers does not support simulation for CHARMS Smart Logic Solvers (CSLS). Simulation for CLSL is supported through virtual machine simulation described below.

Starting with v14.FP2, DeltaV SimulatePro provides improved SIS Logic Solver simulation experience, by supporting the "Save and Restore" capabilities for SIS Logic Solvers simulated in the ProfessionalPLUS and Application Stations.



Simulate for SIS on Standalone PC.

Simulation for DeltaV SIS with Electronic Marshalling

Simulation for DeltaV SIS with Electronic Marshalling uses virtual machine simulation for the DeltaV SZ Controller and Charms Smart Logic Solvers (CSLS). With virtual simulation of DeltaV SIS with Electronic Marshalling you can rigorously test safety logic and operator graphics with no configuration changes required when transferring from simulation to actual production hardware. In addition to CSLS and SZ Controllers simulation, DeltaV SIS with Electronic Marshalling simulation includes all the network components including the Local Safety Network (LSN), the Global Safety Network (GSN) and Local Safety Network Bridge (LSNB).

For more information, see the product data sheet for DeltaV SIS with Electronic Marshalling – Virtual Simulation.

Note: DeltaV SimulatePro does not support "Save and Restore" of virtual machine SZ Controllers or CSLS.

DeltaV Virtual Studio

DeltaV Virtual Studio is an integrated DeltaV application environment designed for easy implementation and management of virtual DeltaV control systems for both off-line and on-line production systems. DeltaV Virtual Studio is used to create, modify, start, stop, and move DeltaV virtual machines. DeltaV Simulate Multi-node virtual workstations are easily created and assigned to host computers using DeltaV Virtual Studio.

Delta¥ Virtual Studio					-
File Help					
By Host By Group		6	6		
ServiceManager DELTAV-HOST	Create VM	Modify Host Rem	ove Host		
APP V12					
DVS_Client	Virtual Machine Na	me Group	Status	Failover	Action
0PER_V12	APP_V12	DeltaV v12 Demo	Hunning	No	Shut Down
ProPlus_v12	OPER V12	DeltaV v12 Demo	Running	No	Shut Down
	PR0 V12	DeltaV v12 Demo	Buncing	No	Shut Down
VSCTLR-1	PtoPlus v12	DeltaV v12 Demo	Bunning	No	Shut Down
	VCIOC-1	DeltaV v12 Demo	Bunning	No	Turn Off
	VSCTLR-1	DeltaV v12 Demo	Bunning	No	Turn Off
Crea	te VM				
_\ _\	Intual Machine Configuration				-
	Template Location:	C:\VM_Templates		-	iT-1
	Host Name:	DELTAV-HOST-1		-	2 Standard Service Pi
	Machine Location:	D:\EmersonVirtualization	\\VMs	*	
	Group	DeitaV v12 Demo			RT1)13/G8/290G8 P
	Configured RAM (MB):	4096			5 MB
	Config and Processors	4		¥.	
	Configured Follower	P.		-	
	- Childer Morter	1.01	see necovery now		
	Data / Magination	[12.2		-	
	Node Tune	12.3	ndarra 71 Bin stal	-	
Current User: DELTAV-HOST-1\Ad	Workstation Configuration File		idows 7 Orimale)		
	Machine Name	Oneutra	dating		
	E Castle Danala Class Co	lobean		-	
	DeltaVAdmin Password	- Corally		_	
- 5	letwork Configuration				
	Virtual Network Card	/irtual Network Name	Deital/ Network Type	-	
	DeltaV Primary	DeltaV Primary	Deltal/ Primary		
	DLink I	Vexey Secondary Not Connected	Unassigned	_	
	Remote Primary	Not Connected	Unassigned		
	Remote Secondary 1	Vot Connected	Unassigned	- 1	
1.	Plant I GN I	Plant I GN	Plant I &N	-	
	Plant I dN I Canc	Not Connected Plane I AN	Unassigned Plant I &N	-	•1

DeltaV Virtual Studio Application.

DeltaV Simulate Multi-node virtual workstations are easy to create and implement using virtual machine templates. These templates allow you to easily add workstations from a single configuration dialog. Simply specify the host computer, enter a computer name, select the DeltaV workstation template, select the network connections from a drop down menu, and press OK. Within a few minutes the new DeltaV workstation will be automatically generated from a prebuilt template. For more information, see the product data sheet for DeltaV Virtual Studio.

Licensing

DeltaV Simulate consists of the following license options.

- DeltaV Simulate, or DeltaV SimulatePro Standalone. A single PC license that can be used only in a training or development system. DeltaV DVDs and an access key are included so you may install DeltaV software on your PC. Communications to other DeltaV workstations or to DeltaV controllers is not supported.
- 2. DeltaV Simulate Standalone with Basic SIS Logic Solver Simulation. Provides all the capabilities of DeltaV Simulate Standalone plus simulation of up to 32 logic solvers (SLS1508) assigned to a workstation; but does NOT include support for SIS Network OPC server.
- **3. DeltaV Simulate ProfessionalPLUS Networked (PPN).** Same capabilities as DeltaV Simulate Standalone, but license enables communication with other DeltaV workstations and DeltaV controllers to form a multiple node training and development system.
- **4. DeltaV Simulate Professional Station Networked (PSN).** The DeltaV Simulate PSN license allows you to perform engineering, configuration, and operations activities in a multi-node system. DeltaV Simulate PSN includes all of the base and optional software available on a normal Professional Station.
- **5. DeltaV Simulate Operator Station Networked (OSN).** The DeltaV Simulate OSN license allows you to perform all operator activities in a multi-node system. Multiple OSN workstations allow you to simultaneously train multiple operators on the same process simulation system.
- **6. DeltaV Simulate Application Station Networked (ASN).** The DeltaV Simulate ASN license includes all standard and optional components available for a normal on-line Application Station in an off-line Simulate Multi-node environment.
- 7. DeltaV SimulatePro—Multi-node Add-on. This license may be assigned in conjunction with DeltaV Simulate PPN or DeltaV Simulate ASN license. The SimulatePro capability enables more memory for module execution (of any type) and a user interface for coordination of module execution. SimulatePro also provides save, restore, speed-up, slowdown, playback, and simulation conversion functionality.

8. DeltaV SIS Logic Solver SimulatePro – Add-on. These licenses may be assigned in conjunction with DeltaV Simulate PPN, ASN, and Standalone licenses. The SIS SimulatePro capability enables simulation of up to 32 logic solvers (SLS1508) for the assigned workstation, plus support for OPC access to logic solver I/O via a SIS Network OPC server. This add-on license does not include DeltaV SimulatePro add-on features which may be added separately.

Subscription Based Licensing

- DeltaV Simulate Multi-Node software licensing starting DeltaV v15.LTS can be only purchased as a one-year, three-year, or five-year subscription which includes software, updates, and support. DeltaV Simulate Multi-Node to be used for off-line simulation only.
- 2. To view the expiration of the Simulate Multi-Node system ID launch Watchit application and use the DongleDriver path. The expiration will appear along with the system ID.
- 3. If a Simulate Multi-Node software license is allowed to expire, the continued use of the software is not permitted. The software will continue running the currently loaded configuration in this unlicensed state, but you will not be able to download any changed configuration to the unlicensed license. Please contact your sales representative to know more about the subscription contract process.

Related Products

 DeltaV Virtual Studio is an integrated DeltaV application environment designed for easy implementation and management of virtual DeltaV control systems for both off-line and on-line production systems. Virtual machine templates are provided for automatic generation and configuration of DeltaV workstations and controller hardware. For more information, see product data sheet for DeltaV Virtual Studio.

- DeltaV Virtual Machine Controller Simulation. For off-line use, virtual hardware controllers provide an effective way to checkout control configuration and I/O assignments for both classic I/O and CHARMS I/O cards. The virtual controllers can be named and configured the same as real controllers so that no configuration changes or module re-assignments are required. S-series and M-series controllers are supported for DeltaV v11.3.1 and later. PK Controllers are supported for v14.3 and later. All virtual machine controllers are available for both DeltaV Virtual Studio and VMware environments. For more information see product data sheet for DeltaV Virtual Machine Controller Simulation.
- DeltaV Virtual CHARMS I/O Card Simulation.
 Simulation of CHARMS I/O cards using virtual machines running in a workstation PC. Virtual CHARMS I/O cards function in DeltaV the same as real CHARMS I/O cards and can be used for rigorous checkout of I/O assignments, operator displays, and control functionality. For more information, see product data sheet for DeltaV Virtual CHARMS I/O Card Simulation.
- DeltaV SIS with Electronic Marshalling Virtual Simulation. Provides virtualization of SIS hardware components for rigorous testing of CSLS safety logic and operator graphics. For more information see product data sheet for DeltaV SIS with Electronic Marshalling
 Virtual Simulation.
- DeltaV Virtual Ethernet I/O Card Simulation.
 Provides DeltaV Ethernet I/O Card (EIOC) Simulation from

 a host computer using either DeltaV Virtual Studio or
 VMware, which eliminates the need for hardware during FAT
 or other testing scenarios. For more information, see product
 data sheet for DeltaV Virtual Ethernet I/O Card Simulation.

Note: DeltaV Virtual Machine (VM) Controllers, VM CHARMs I/O Cards, VM Ethernet I/O Cards and VM SIS SZ/CSLS components are rolled out mainly for engineering development and testing purposes. Limitations may apply if the intent is to use them continuously in development to support ongoing production. Please consult Emerson sales teams for using these VM nodes for this use case.

Ordering Information

Description: DeltaV Simulate—Single PC	Perpetual Model Number	
DeltaV Simulate, Standalone	VE9921RxxxLyy	
DeltaV SimulatePro, Standalone	VE9922RxxxLyy	
DeltaV Simulate, Standalone with Basic SIS Logic Solver Simulation	VE9923RxxxLyy	
Description: DeltaV Simulate—Multi-Node		
DeltaV Simulate, ProfessionalPLUS Networked (PPN)	VX2101RxxxLyy	
DeltaV Simulate, Professional Station Networked (PSN)	VX2102S01	
DeltaV Simulate, Application Station Networked (ASN)	VX2201S01	
DeltaV Simulate, Operator Station Networked (OSN)	VX2104S01	
Description: DeltaV SimulatePro—Multi-Node		
DeltaV SimulatePro—Multi-node (added to DeltaV Simulate PPN and/or DeltaV Simulate ASN to obtain the increased capabilities of SimulatePro)	VX2207S01	
Description: DeltaV SIS Logic Solver SimulatePro—Add-On		
DeltaV SIS Logic Solver SimulatePro —Full SIS Simulation Add-on for DeltaV Standalone (Add-on for VE9921 or VE9922)	VE3201	
DeltaV SIS Logic Solver SimulatePro —Full SIS Simulation Add-on for DeltaV Multi-Node (Add-on for VX2101 or VX2201)	VX3201	

*Note: DeltaV SIS Logic Solver Simulate supports the DeltaV SIS Logic Solver SLS1508. DeltaV SIS Logic Solver Simulate does not support CHARMS Smart Logic Solver (CSLS). DeltaV SIS Logic Solver SimulatePro Add-on license does not include DeltaV SimulatePro features which may be purchased separately.

*Note: Product numbers with RxxxLyy are for multiple releases where 'xxx' represents the DeltaV major version (e.g., 133 for DeltaV v13.3), and 'yy' is a two digit code representing the language (e.g. 39 for English).

*Note: DeltaV Simulate may not be used in or be connected to any system involving a live process. It must be used only for software configuration development, process and control design, system operation checkout and training in a strictly off-line environment.

*Note: DeltaV software is only tested and supported on DeltaV workstation PC's.

Subscription

DeltaV Simulate Multi-Node software licensing starting DeltaV v15.LTS can be only purchased as a one-year, three-year, or five-year subscription which includes software, updates, and support.

Description: DeltaV Simulate—Multi-Node PC	*Subscription Model Number	
DeltaV Simulate, ProfessionalPLUS Networked (PPN)	VX2101SwRxxxLyy_YyFYzz	
DeltaV Simulate, Professional Station Networked (PSN)	VX2102SwS001_YyFYzz	
DeltaV Simulate, Application Station Networked (ASN)	VX2201SwS001_YyFYzz	
DeltaV Simulate, Operator Station Networked (OSN)	VX2104SwS001_YyFYzz	
Description: DeltaV SimulatePro—Multi-Node		
DeltaV SimulatePro—Multi-node (added to DeltaV Simulate PPN and/or DeltaV Simulate ASN to obtain the increased capabilities of SimulatePro)	VX2207SwS001_YyFYzz	
Description: DeltaV SIS Logic Solver SimulatePro—Add-On		
DeltaV SIS Logic Solver SimulatePro —Full SIS Simulation Add-on for DeltaV Multi-Node (Add-on for VX2101 or VX2201 Subscription model numbers)	VX3201SwS001_YyFYzz	

Note: These subscription model numbers are for initial subscriptions only; model numbers for renewals are listed separately in the price book.

**w represents the length of the subscription term in years (1, 3, or 5).

**y represents the specific year of the subscription term (1, 2, 3, 4, or 5).

**zz represents a two-digit indicator of the year of purchase (e.g. 23).

Note: For existing customers with perpetual Simulate Multi-Node licenses who wish to expand and/or upgrade their DeltaV Simulate solution, please contact your local sales office.

©2023, Emerson. All rights reserved.

The Emerson logo is a trademark and service mark of Emerson Electric Co. The DeltaV logo is a mark of one of the Emerson family of companies. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while diligent efforts were made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice.

Contact Us (a) www.emerson.com/contactus

